



SIDER-CRETE, INC.

153 Regur Road
Hawkinsville, GA 31036 – USA

Ph: 478.892.9800

www.sider-crete.com

SIDER-FIX POLY

A NEXT GENERATION CLEAR, HEAVY-DUTY POLYURETHANE-HYBRID SEALER, WHICH PENETRATES WITH THE SURFACE TO BE TREATED TO GIVE A DEEP, PENETRATING ABRASIVE AND CHEMICAL PROTECTION OF MASONRY SURFACES.

1.0 DESCRIPTION

1.1 General

A next-generation clear, penetrating POLYURETHANE-HYBRID reinforcing sealer that when applied to concrete or masonry, provides a very hard, dust repellent, chemical resistant and watertight surface.

2.0 MATERIALS

2.1 Sider-Fix Poly

Sider-Fix Poly is formulated to deeply penetrate the pores and capillaries of old or recently cured concrete or stone and brick surfaces with a clear coating, producing an extremely water repellent surface. It is suitable for use on interior or exterior horizontal or vertical surfaces.

Sider-Fix Poly provides protection against:

- De-icing salts
- Moisture
- Weathering
- Freeze induced scaling

Sider-Fix Poly is ideally suited to protect roads, sidewalks, parking decks, parking ramps, wall and bridges exposed to weathering.

3.0 INSTALLATION

3.1 Surface preparation:

Surfaces must be clean, cured, dust-free and free of release agents or contamination. Remove all paint, loose or damaged material and rubber marks from the surface.

3.2 Application:

Surfaces should receive a minimum of two cross-coats applied with a low-pressure sprayer, standard paintbrush or paint roller. Allow **Sider-Fix Poly** to penetrate the surface and apply a second coat before the first coat dries. Provide adequate ventilation of area to be treated and use protective goggles and rubber gloves during application.

3.3 Limitations

Do not apply to dry or frozen surfaces. Protect from rain, freezing and thawing surfaces. Apply when ambient temperatures are above 45° F (8° C) and below 90° F (32° C) For application outside of these temperature ranges, please contact Sider-Crete, Inc technical support for additional information.

4.0 MISCELLANIOUS

4.1 Packaging

5-gallon (18.9 liters) pail

4.2 Coverage

800 sq. ft. per 5 gallon

(Coverage is approximated and is given for estimating purposes only. Actual jobsite coverage may vary according to substrate conditions and application techniques.)

4.3 Technical Application Assistance

For technical inquiries during normal business hours, contact Sider-Crete, Inc. toll free at 888-743-3750.

4.4 Storage and Shelf Life

Shelter in a dry environment from extreme heat, direct sunlight, rain and freezing. Shelf life is 6 months in the original sealed packaging properly sheltered in a dry environment.

4.5 Commercial Names **SIDER-FIX POLY**

*And now, enjoy using **SIDER-FIX POLY** and benefit from this revolutionary technology developed by Sider-Crete, Inc., innovative leaders in the construction industry since 1937.*

While every effort has been made to be comprehensive and accurate, the publisher cannot accept any liability for omissions or errors. Users should contact Sider-Crete for the product(s) referred to in this specification to ensure that any information used to make decisions about the product is as up-to-date and complete as possible.