



SIDER-CRETE, INC.

153 Regur Road
Hawkinsville, GA 31036 – USA
Ph: 478.892.9800
www.sider-crete.com

SIDER-ROOF

SEAMLESS ELASTOMERIC WATERPROOFING CONCRETE ROOF COATING

1.0 DESCRIPTION

1.1 General

Sider-Roof is a unique system that combines strength, excellent waterproofing performance, flexibility and reflectivity to protect inaccessible roofs, concrete roofing or cement-based roofing systems against severe weather and pollutants.

2.0 INSTALLATION

2.1 Surface preparation

Prime surfaces using **Sider-Roof Primer** (refer to specifications). Allow a minimum of 24 hours and maximum of 72 hours days after the initial application of the **Sider-Roof Primer** before applying **Sider-Roof**. Surfaces must be dry prior to the application of **Sider-Roof**.

2.2 Mixing Instructions

Sider-Roof has excellent suspension and requires minimal stirring. **DO NOT THIN.**

2.3 Application

Sider-Roof is a two-coat application process. Simply apply **Sider-Roof** with a soft brush, roller or airless sprayer. Apply the gray base coat and allow a minimum of 24 hours and maximum of 72 hours after the initial application before applying the white finish coat.

2.4 Limitations

Apply **Sider-Roof** when surface and ambient temperatures are above 50° F and below 95° F during application and drying period. Do not apply when rain is in the forecast. Application during low temperature or high humidity will extend drying time. Allow 24 hours for coating to dry prior to being subjected to rain. **KEEP FROM FREEZING.**

2.5 Maintenance

It is recommended that installation be checked on a regular maintenance schedule. Small area touch up can be made, if needed, following the recommended application procedures.

3.0 MISCELLANEOUS

3.1 Packaging

5 gallon pails

3.2 Coverage

250 sq. ft. per 5 gallons per coat (grey base coat and white finish coat).

3.3 Colors

Sider-Roof is available white and grey base-coat (custom colors are available upon request).

3.4 Technical Application Assistance

For technical inquiries, contact Sider-Crete, Inc. at **Toll Free: 888-743-3750**.

3.5 Professional Qualifications

Installation shall be performed by contractors with a minimum of 5 years documented experience in roof coatings application or approved by Sider-Crete, Inc. All applicators should be able to provide several references from general contractors, architects or other applicable references for review by Sider-Crete, Inc.

3.6 Storage and Shelf Life

Store in a dry environment, away from direct sunlight, rain, and freezing temperatures.

Shelf life is 6 months in the original sealed packaging, properly sheltered in a dry environment.

3.7 Commercial Names

SIDER-ROOF

*And now, enjoy using **SIDER-ROOF** and benefit from this revolutionary technology developed by Sider-Crete, Inc., innovative leaders in the construction industry since 1937.*

While every effort has been made to be comprehensive and accurate, the publisher cannot accept any liability for omissions or errors. Users should contact Sider-Crete for the product(s) referred to in this specification to ensure that any information used to make decisions about the product is as up-to-date and complete as possible.