



SIDER-CRETE, INC.

153 Regur Road
Hawkinsville, GA 31036 – USA
Ph: 478.892.9800
www.sider-crete.com

SIDER-STOP

THE QUICK SETTING WATERPROOFING HYDRAULIC BINDER REPAIR MORTAR

1.0 DESCRIPTION

1.1 General

Sider-Stop is a quick setting waterproofing hydraulic-binder repair mortar designed for concrete and masonry surfaces. **Sider-Stop** is formulated to set in minutes to stop water leaks originating from cracks or holes in walls or ceilings prior to the application of a waterproofing or water repellent treatment. **Sider-Stop** is prepared in small quantities and used as needed to stop active water leaks or any type of water infiltration.

2.0 MIXING INSTRUCTIONS

2.1 Sider-Stop

Mix one part of clean potable water to 3 parts of **Sider-Stop** and mix by hand, or by using a drill and paddle.

3.0 INSTALLATION

3.1 Application

Surface preparation:

Surfaces must be free of all bond-inhibiting materials including dirt, efflorescence, release agents and other foreign particles. Remove paint, loose or damaged materials by water blasting, pressure washing, sandblasting or mechanical wire brushing.

Application:

Apply as soon as mixed directly to the area to be sealed, as it will set in minutes. In case of running water, shape **Sider-Stop** into a ball with your hands and apply as soon as possible to the area to be sealed. Hold the mortar in place for 3 minutes by pressing with your hands; then waterproof the entire surface with waterproofing or water repellent agent such as Sider-Proof T, Sider-Proof FF, etc...

3.2 Limitations

Apply **Sider-Stop** when surface and ambient temperatures are above 41° F (5° C) and below 95° F (35° C) during application and drying period. Do not apply to overheated, excessively dry or frozen substrates, nor during periods of high winds.

4.0 MISCELLANEOUS

4.1 Packaging

55 lb. (25 kg) bag of powder

4.2 Technical Assistance

For technical support, contact Sider-Crete, Inc. at **Toll Free: 888-743-3750**.

4.3 Storage and Shelf Life

Shelter in a dry environment from extreme heat, direct sunlight, rain and freezing. Shelf life is 6 months in the original sealed packaging properly sheltered.

4.4 Commercial Name

SIDER-STOP

*And now, enjoy using **SIDER-STOP** and benefit from this revolutionary technology developed by Sider-Crete, Inc., innovative leaders in the construction industry since 1937.*

While every effort has been made to be comprehensive and accurate, the publisher cannot accept any liability for omissions or errors. Users should contact Sider-Crete for the product(s) referred to in this specification to ensure that any information used to make decisions about the product is as up-to-date and complete as possible.